INOX	Saladette
SALADETTE	► GN1/1 ► OPEN TOP

<u>CR 92A</u>



GENERAL FEATURES

GN1/1 Refrigerated saladette (OPEN TOP)		
Stainless Steel exterior and interior		
Static Cooling		
Automatic compressor cycle defrost	•	
Foaming Agent Cyclopentane (45mm per side)		
Digital Thermostat	•	
Sliding engine room for a manageble after sales servicing	•	
Plastic thermal-braker as chamber body frame	•	
Easy removable condenser filter	•	
Separated plastic water tray	•	
Front panel tilted holes for better air circulation	•	
Adjustable shelves GN1/1: 2 Pcs	•	
Self closing door (New inner embossed design for a better sealing)	•	
Removable Gasket	•	
Engine room lock fitted as standard	•	
N.2 Adjustable feet in the front + N.4 fix rollers		
Holder spacer for GN pans with "hook" design (included)		
Energy efficiency class: -		

TECHNICAL SPECIFICATIONS

Capacity	269L
Temperature	+0° ~ +8°C
Consumption	2.453 kWh/24h
Rated Power	182 W
Noise level	50 dB(A)
Net Weight	75 Kg
Gross Weight	92 Kg
External Dimensions (WxDxH mm)	1045x700x883
Internal Dimensions (WxDxH mm)	955x586x502
Packaging dimensions (WxDxH mm)	1100x750x1030
Loading quantities 20′/40′/40′HQ	30/60/60

(€ ℃

RoHS

CERTIFICATION



() () () () () () () () () () () () () (GAS R600a $ \begin{bmatrix}] [45 mm]] $	CLIMATIC CLASS 36°C
	HD)	P A
		DETAILS
COOL HEAD		C.
Main switch and digital thermostat fitted as standard	Curved edge for easy cleaning	Engine room lock fitted as standard
Anti-condensation themal-braker on door frame	Inner embossed door design for a better sealing	Sliding engine easy to pull out for manageble after sales servicing
Holder spacer for GN pans with "hook" design	Inner assistance fan	

PRODUCT DIMENSIONS



